



MAPELASTIC AQUADEFENSE
Declaration of Performance
No CPR-IT1/1112

DECLARATION OF PERFORMANCE No CPR-IT1/1112

- 1) Unique identification code of the product-type: **MAPELASTIC AQUADEFENSE**
- 2) Intended uses: **Dispersion liquid-applied water impermeable product (DM O1), for all external installations and swimming pools beneath ceramic tiling (bonded with a C2 adhesive in accordance with EN 12004).**
- 3) Manufacturer: **Mapei SpA - Via Cafiero, 22 - 20158 - Milano - Italia (Italy) - www.mapei.it**
- 4) Harmonized standards: **EN 14891:2012, EN 14891:2012/AC:2012**

No: Notified bodies:

0370 LGAI TECHNOLOGICAL CENTER, S. A.(Applus+)

- 5) Performances declared and Assessment and Verification of Constancy of Performance (AVCP):

Essential characteristics	Performances	AVCP
Initial tensile adhesion strength:	$\geq 0,5 \text{ N/mm}^2$	4
Water tightness:	no penetration	3
Crack bridging ability:	under standard conditions (+23°C) $\geq 0,75 \text{ mm}$ at low temperature (-5°C) $\geq 0,75 \text{ mm}$	4
Durability of initial tensile adhesion: - against climate/heat ageing action: - against water/humidity action: - against contact with lime water: - against freeze and freeze-thaw cycles:	$\geq 0,5 \text{ N/mm}^2$ $\geq 0,5 \text{ N/mm}^2$ $\geq 0,5 \text{ N/mm}^2$ $\geq 0,5 \text{ N/mm}^2$	4
Release of dangerous substances:	NPD	-



MAPELASTIC AQUADEFENSE
Declaration of Performance
No CPR-IT1/1112

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Lorenzo Martino – Corporate Quality Management**

Milano, 20/07/2026

A handwritten signature in blue ink, reading "Lorenzo Martino", positioned above a horizontal dotted line.

The DoP in PDF format are available on our website.

<i>Revision 10 notes:</i>	<i>Updating to points: 1</i>
---------------------------	------------------------------

REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) No 1907/2006 and following amendments are indicated in the Safety Data Sheet that the manufacturer makes available on the website along with this current Declaration of Performance.

 0370	 Via Cafiero, 22 - 20158 - Milano - Italia (Italy) www.mapei.it																
<p style="text-align: center;">24 CPR-IT1/1112 EN 14891 MAPELASTIC AQUADEFENSE</p> <p>Dispersion liquid-applied water impermeable product (DM O1), for all external installations and swimming pools beneath ceramic tiling (bonded with a C2 adhesive in accordance with EN 12004).</p>																	
<table><tr><td>Initial tensile adhesion strength:</td><td>≥ 0,5 N/mm²</td></tr><tr><td>Water tightness:</td><td>no penetration</td></tr><tr><td>Crack bridging ability:</td><td>under standard conditions (+23°C) ≥ 0,75 mm at low temperature (-5°C) ≥ 0,75 mm</td></tr><tr><td>Durability of initial tensile adhesion:</td><td></td></tr><tr><td>- against climate/heat ageing action:</td><td>≥ 0,5 N/mm²</td></tr><tr><td>- against water/humidity action:</td><td>≥ 0,5 N/mm²</td></tr><tr><td>- against contact with lime water:</td><td>≥ 0,5 N/mm²</td></tr><tr><td>- against freeze and freeze-thaw cycles:</td><td>≥ 0,5 N/mm²</td></tr></table>		Initial tensile adhesion strength:	≥ 0,5 N/mm ²	Water tightness:	no penetration	Crack bridging ability:	under standard conditions (+23°C) ≥ 0,75 mm at low temperature (-5°C) ≥ 0,75 mm	Durability of initial tensile adhesion:		- against climate/heat ageing action:	≥ 0,5 N/mm ²	- against water/humidity action:	≥ 0,5 N/mm ²	- against contact with lime water:	≥ 0,5 N/mm ²	- against freeze and freeze-thaw cycles:	≥ 0,5 N/mm ²
Initial tensile adhesion strength:	≥ 0,5 N/mm ²																
Water tightness:	no penetration																
Crack bridging ability:	under standard conditions (+23°C) ≥ 0,75 mm at low temperature (-5°C) ≥ 0,75 mm																
Durability of initial tensile adhesion:																	
- against climate/heat ageing action:	≥ 0,5 N/mm ²																
- against water/humidity action:	≥ 0,5 N/mm ²																
- against contact with lime water:	≥ 0,5 N/mm ²																
- against freeze and freeze-thaw cycles:	≥ 0,5 N/mm ²																

The manufacturer supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.